

Art Specs

Art must be in CMYK and all pms colors called out.
Please refrain from using any stroke under .5 pts. (no hairlines)
Minimum of .125" bleed

Sending Art

CD or DVD with art work, fonts, images, print ready pdf, and physical color proof of art.

Art can also be loaded onto our web site. Please upload a print ready pdf. E-mail or contact your account representative after artwork has been uploaded.

User: hoppmann
Password: upload

Art can be e-mailed if file size is under 2mb.

Contact Info

Hoppmann Group
3000 N. 117th street
Wauwatosa, WI 53222

www.hoppmanngroup.com

P.414.476.2040
F.414.476.3006



Presstek 34Direct Image Offset -

.354" Gripper
3.54" x 3.94" minimum sheet size
13.39" x 18.125" maximum sheet size
12.99" x 17.72" maximum image area
.015" maximum sheet thickness

Sakurai 472-ED 4 Color Offset -

.625" Gripper
10" x 14" minimum sheet size
20.5" x 28.75" maximum sheet size
.015" maximum sheet thickness

Man Roland 202 2 Color Offset -

.375" Gripper
9.5" x 12.5" minimum sheet size
20.5" x 29" maximum sheet size
.030" maximum sheet thickness

Ryobi 3302M 2 Color Offset -

.312" Gripper
4.5" x 5.5" minimum sheet size
13.375" x 17.75" maximum sheet size
.012" maximum sheet thickness

Hamada 555 2 Color Offset -

.375" Gripper
10" x 15" maximum sheet size
.012" maximum sheet thickness

Davidson 501 Single Color Offset -

.375" Gripper
3.5" x 4" minimum sheet size
10" x 14" maximum sheet size
.012" maximum sheet thickness

Davidson 500 Offset -

.375" Gripper
10" x 15" maximum sheet size
.012" maximum sheet thickness

Sunraise SR 12" Thermographer -

11.5" x 15" maximum sheet size single sided

Ikon 650 4 Color Digital Press

13" x 19.2" (12.5" x 18.75" image area)
110 # maximum sheet thickness



Heidelberg Cylinder Die Cutter SBBZ -

1/2" Gripper (Minimum)- Side guide can be on either side
10" x 13" minimum sheet size
22" x 31" maximum sheet size
.020" maximum sheet thickness

Heidelberg Windmill Letterpresses -

Press used for imprinting, numbering, scoring, perforating, face cutting, die cutting. Can perf and number at the same time, but the perf will print.

1/4" Gripper minimum
3/8" Gripper is needed when a die is involved
1 1/2" x 2 3/4" minimum sheet size
10 1/4" x 15" maximum sheet size
.024" maximum sheet thickness
To Register: Top of sheet - Gripper (10 1/4")
Left side - guide (15")

Kluge Foil Stamper -

Used for foil stamping ,die cutting and embossing.

No restrictions for Gripper
3.5" x 4" minimum sheet size
19" x 24.75" maximum sheet size
Image size max has restrictions, please call
2000 maximum impressions per hour

Kluge Foil Stamper -

Used for foil stamping ,die cutting and embossing.

No restrictions for Gripper
3.5" x 4" minimum sheet size
17" x 19" maximum sheet size
12" x 18" maximum image size
2000 maximum impressions per hour

Other Finishing Services -

Cutting
Cerlox Binding
Letterpress Scoring
Perforating
Round Cornering
Padding
Drilling
Grommeting
Folding
Collating
Saddle Stitching
OM Folder
Marathon Auto Pocket Folder/Gluer
Index Tabbing
Brushless Card Slitter

Workflow System

Fully integrated CTP Agfa Apogee X workflow solution. This allows customers to send either native files or print ready pdfs. Hoppmann creates an integrated proof that allows you to see a proof that is the same file that we plate. We are able to use conventional roset dot or state of the art sublima XM screening technology to achieve optimum print and color clarity.

Proofing Specs

Oris Color Tuner software driving an Epson 7600 printer. This allows us to print color matched, press accurate proofs. Proofing system is fingerprinted to our press to assure highest color match standards.

Programs

Quark 7.0
Adobe CS2 - Illustrator, InDesign,
and Photoshop

Other formats available, please
contact our prepress department
before sending art.



3000 N. 117th Street
Wauwatosa, WI 53222

Tel 414.476.2040
Fax 414.476.3006

hoppmanngroup.com